

## Liberty® Radiant L234

Small Direct Vent Gas Insert



#### **Standard Features**

- ✓ Natural gas
- **NEW ☑** Safety screen
- **NEW** ☑ Proflame remote control
  - ☑ Direct spark ignition
  - ☑ Ceramic safety glass
  - ✓ Log set with glowing embers
  - ☑ 30° angled flue for versatile installation
  - ☑ Variable speed blower
  - ✓ Installation spacer
  - ☑ Flame height adjustment control
  - ☑ Limited lifetime warranty

### **Optional Features**

- ☐ Low profile faceplate
- ☐ Custom backing plate
- ☐ Adjustable hearth riser
- ☐ Brick panels
- ☐ Regency flex venting
- ☐ Basic or programmable thermostat
- ☐ 3" to 2" air intake reducer
- ☐ Propane conversion kit

Specifications	Natural Gas	Propane
Input (BTU)	23,500	21,500
Turn down to (BTU)	12,500	11,000
EnerGuide Rating*	63.3%	64.5%
Efficiency (steady state)	74%	74%

\* for Canada only


Min. Fireplace Opening	
Width (front)	25"
Width (rear)	16"
Height	20"
Depth	14"
Depth (with spacer)	15-5/8"





# Liberty® Radiant L234 Small Direct Vent Gas Insert

#### **Dimensions**

Dimensions	L234
Flue size	3"
А	14-3/4"
В	24-3/4"
C	22-13/16"
D	32-7/8"
Е	16-15/16"
F	14-11/16"
G	2-1/2"









Openings

Openings	L234	
А	14"	
В	15-5/8"	
С	17"	
D	25"	
Е	16"	





Clearances

Clearances	L234
Α	8"
В	56"
С	21"
D	12"
E	60"
F	36"
G	1-1/2"
Н	28"
1	12"

